



# Industrial Business Link

SERVING ALL YOUR NEEDS FOR PIPE, PIPE-FITTINGS, FLANGES, VALVES, GASKETS & STUD BOLTS

**SPECIALIST IN**  
 Carbon Steel  
 Stainless Steel  
 Alloy Steel  
 Low Temperature  
 &  
 High Pressure  
 Materials

## STANDARD PIPE SCHEDULE & WEIGHT MEASUREMENT (LBS/KG)

SIZE OD INCH OD MM	SCHEDULE (SCH)	W.T (INCH)	LBS/ FOOT	W.T (MM)	KG/ METER	SIZE OD INCH OD MM	SCHEDULE (SCH)	W.T (INCH)	LBS/ FOOT	W.T (MM)	KG/ METER	SIZE OD INCH OD MM	SCHEDULE (SCH)	W.T (INCH)	LBS/ FOOT	W.T (MM)	KG/ METER	
1/4 0.540" 13.7mm	10S	.065	.3297	1.65	0.51	6 6.625" 168.3mm	5S	.109	7.585	2.77	11.55	18 (Cont.)	120	1.375	244.14	34.93	363.56	
	40STD, 40S	.088	.4248	2.24	0.63		10S	.134	9.289	3.40	14.13		140	1.562	274.22	39.67	408.26	
	80XS, 80S	.119	.5351	3.02	0.80		40STD, 40S	.280	18.97	7.11	28.26		160	1.781	308.50	45.24	459.37	
3/8 0.675" 17.1mm	10S	.065	.4235	1.65	0.64	8 8.625" 219.1mm	5S	.109	9.914	2.77	15.09	20 20.000" 508mm	10	.250	52.73	6.35	78.55	
	40STD, 40S	.091	.5676	2.31	0.84		10S	.148	13.40	3.76	20.37		20, STD	.375	78.60	9.53	117.15	
	80XS, 80S	.126	.7388	3.20	1.10		20	.250	22.36	6.35	33.31		30, XS	.500	104.13	12.70	155.12	
1/2 0.840" 21.3mm	5S	.065	.5383	1.65	0.82	10 10.750" 273.1mm	5S	.109	9.914	2.77	15.09	22 22.000" 559mm	40	.594	123.11	15.09	183.42	
	10S	.083	.6710	2.11	1.01		60	.812	16.64	4.25	24.83		60	.812	166.40	20.62	247.83	
	40STD, 40S	.109	.8510	2.77	1.27		80	1.031	20.87	5.25	31.17		80	1.031	208.87	26.19	311.17	
	80XS, 80S	.147	1.088	3.73	1.62		100	1.281	25.10	6.35	38.53		100	1.281	256.10	32.54	381.53	
	160	.188	1.309	4.78	1.95		120	1.500	29.67	7.62	44.49		120	1.500	296.37	38.10	441.49	
3/4 1.050" 26.7mm	5S	.065	.6838	1.65	1.04	12 12.750" 323.9mm	60	.406	35.64	10.31	45.58	24 24.000" 609.6mm	140	1.750	341.09	44.45	508.11	
	10S	.083	.8572	2.11	1.31		80XS, 80S	.500	43.39	12.70	64.64		160	1.969	379.17	50.01	564.81	
	40STD, 40S	.113	1.131	2.87	1.69		100	.594	50.95	15.09	75.92		22 22.000" 559mm	10	.250	58.07	6.35	86.54
	80XS, 80S	.154	1.474	3.91	2.20		120	.719	60.71	18.26	90.44			20, STD	.375	86.61	9.53	129.13
	160	.219	1.944	5.56	2.90		140	.812	67.76	20.62	100.92			30, XS	.500	114.81	12.70	171.09
1 1.315" 33.4mm	5S	.065	.8678	1.65	1.33	14 14.000" 355.6mm	160	.906	74.69	23.01	111.27	26 26.000" 660.4mm	60	.875	197.41	22.23	294.25	
	10S	.109	1.404	2.77	2.13		10	.250	15.19	3.40	23.08		80	1.125	250.81	28.58	375.23	
	40STD, 40S	.133	1.679	3.38	2.50		20	.250	28.04	6.35	41.77		100	1.375	302.88	34.93	451.42	
	80XS, 80S	.179	2.172	4.55	3.24		30	.307	34.24	7.80	51.03		120	1.625	353.61	41.28	527.02	
	160	.250	2.844	6.35	4.24		40STD, 40S	.365	40.48	9.27	60.31		140	1.875	403.00	47.63	600.63	
1 1/4 1.660" 42.2mm	5S	.065	1.107	1.65	1.68	16 16.000" 406.4mm	80	.594	64.43	15.09	96.01	28 28.000" 711.2mm	100	1.375	302.88	34.93	451.42	
	10S	.109	1.806	2.77	2.76		100	.844	89.29	21.44	133.06		120	1.625	353.61	41.28	527.02	
	40STD, 40S	.140	2.273	3.56	3.39		120, XXS	1.000	104.13	25.40	155.15		140	1.875	403.00	47.63	600.63	
	80XS, 80S	.191	2.997	4.85	4.47		160	1.125	115.64	28.58	172.33		160	2.125	451.06	53.98	672.26	
	160	.250	3.765	6.35	5.61		5S	.156	22.18	3.96	31.89		30 30.000" 762mm	10	.250	58.07	6.35	86.54
1 1/2 1.900" 48.3mm	5S	.065	1.274	1.65	1.95	10S	.180	24.20	4.57	36.73	20, STD	.375		86.61	9.53	129.13		
	10S	.109	2.085	2.77	3.10	20	.250	33.38	6.35	49.73	30, XS	.500		114.81	12.70	171.09		
	40STD, 40S	.145	2.718	3.68	4.05	30	.330	43.77	8.38	65.20	40	.875		197.41	22.23	294.25		
	80XS, 80S	.200	3.631	5.08	5.41	STD, 40S	.375	49.56	9.53	73.88	60	1.125		250.81	28.58	375.23		
	160	.281	4.859	7.14	7.25	40	.406	53.53	10.31	79.73	80	1.375	302.88	34.93	451.42			
2 2.375" 60.3mm	5S	.065	1.604	1.65	2.44	18 18.000" 457.2mm	60	.562	73.15	14.27	108.96	42 42.000" 1067mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		80	.688	88.63	17.48	132.08		20, XS	.500	114.81	12.70	171.09	
	40STD, 40S	.154	3.653	3.91	5.44		100	.844	107.32	21.44	159.91		30	.625	182.73	15.88	271.21	
	80XS, 80S	.218	5.022	5.54	7.48		120	1.000	125.49	25.40	186.75		40	.875	197.41	22.23	294.25	
	160	.344	7.462	8.74	11.11		140	1.125	139.67	28.58	208.14		60	1.375	302.88	34.93	451.42	
2 1/2 2.875" 73.0mm	5S	.065	1.274	1.65	1.95	20 20.000" 508mm	160	1.312	160.27	33.32	238.76	32 32.000" 813mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.085	2.77	3.10		10	.250	36.71	6.35	54.69		20, STD	.375	86.61	9.53	129.13	
	40STD, 40S	.145	2.718	3.68	4.05		20	.312	45.61	7.92	67.90		30, XS	.500	114.81	12.70	171.09	
	80XS, 80S	.200	3.631	5.08	5.41		30, STD	.375	54.57	9.53	81.33		40	.625	182.73	15.88	271.21	
	160	.281	4.859	7.14	7.25		40	.438	63.44	11.13	94.35		60	.875	197.41	22.23	294.25	
3 3.500" 88.9mm	5S	.065	1.604	1.65	2.44	22 22.000" 559mm	XS, 80S	.500	65.42	12.70	97.46	24 24.000" 609.6mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		60	.562	73.15	14.27	108.96		20, XS	.500	114.81	12.70	171.09	
	40STD, 40S	.154	3.653	3.91	5.44		80	.688	88.63	17.48	132.08		30	.625	182.73	15.88	271.21	
	80XS, 80S	.218	5.022	5.54	7.48		100	.844	107.32	21.44	159.91		40	.875	197.41	22.23	294.25	
	160	.344	7.462	8.74	11.11		120, XXS	1.000	125.49	25.40	186.75		60	1.375	302.88	34.93	451.42	
4 4.500" 114.3mm	5S	.065	1.604	1.65	2.44	24 24.000" 609.6mm	140	1.125	139.67	28.58	208.14	26 26.000" 660.4mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		160	1.312	160.27	33.32	238.76		20, STD	.375	86.61	9.53	129.13	
	40STD, 40S	.154	3.653	3.91	5.44		10	.250	36.71	6.35	54.69		30, XS	.500	114.81	12.70	171.09	
	80XS, 80S	.218	5.022	5.54	7.48		20	.312	45.61	7.92	67.90		40	.625	182.73	15.88	271.21	
	160	.344	7.462	8.74	11.11		30, STD	.375	54.57	9.53	81.33		60	.875	197.41	22.23	294.25	
5 5.563" 141.3mm	5S	.065	1.604	1.65	2.44	26 26.000" 660.4mm	40	.438	63.44	11.13	94.35	28 28.000" 711.2mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		XS	.500	72.09	12.70	107.39		20, STD	.375	86.61	9.53	129.13	
	40STD, 40S	.154	3.653	3.91	5.44		60	.594	85.05	15.09	126.71		30, XS	.500	114.81	12.70	171.09	
	80XS, 80S	.218	5.022	5.54	7.48		80	.750	106.13	19.05	158.10		40	.625	182.73	15.88	271.21	
	160	.344	7.462	8.74	11.11		100	.938	130.85	23.83	194.96		60	.875	197.41	22.23	294.25	
6 6.625" 168.3mm	5S	.065	1.604	1.65	2.44	28 28.000" 711.2mm	120	1.094	150.90	27.79	224.65	30 30.000" 762mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		140	1.250	170.21	31.75	253.56		20, XS	.500	114.81	12.70	171.09	
	40STD, 40S	.154	3.653	3.91	5.44		160	1.406	189.10	35.71	281.70		30	.625	182.73	15.88	271.21	
	80XS, 80S	.218	5.022	5.54	7.48		10	.250	42.05	6.35	62.64		40	.875	197.41	22.23	294.25	
	160	.344	7.462	8.74	11.11		20	.312	52.27	7.92	77.87		60	1.375	302.88	34.93	451.42	
8 8.625" 219.1mm	5S	.065	1.604	1.65	2.44	30 30.000" 762mm	40, XS	.500	82.77	12.70	123.30	32 32.000" 813mm	10	.250	58.07	6.35	86.54	
	10S	.109	2.638	2.77	4.01		60	.656	107.5	16.66	160.12		20, STD	.375	86.61	9.53	129.13	
	40STD, 40S	.154	3.653	3.91	5.44		80	.844	136.61	21.44	203.53		30, XS	.500	114.81	12.70	171.09	
	80XS, 80S	.218	5.022	5.54	7.48		100	1.031	164.82	26.19	245.56		40	.875	197.41	22.23	294.25	
	1																	