

209, 2nd Floor, Landmark Plaza, Muhammad Bin Qasim Road, Off. I. I. Chundrigar Road, Karachi-74200, Pakistan. Phone: (92-21) 2218028-29, Fax: (92-21) 2218337 E-mail: info@iblink.com.pk, iblink@cyber.net.pk

### SPECIALIST IN Carbon Steel Stainless Steel Alloy Steel Low Temperature

High Pressure Materials

# Malleable Specifications

# MALLEABLE THREADED FITTINGS

# Standard Class 150 Specifications:

ANSI B1.20.1, Threads. B16.3, Dimensions, Pressure Rating.

A.S.T.M. A197, Material, A153, Galvanizing.

Federal Spec. WWP 521

Pressure Ratings: 150 p.s.i. – Saturated Steam

300 p.s.i. - At 150 degrees W.O.G.

U.L. Listed Where Applicable

Extra Heavy Class 300 Specifications:

ANSI B1.20.1, Threads, B16.3, Dimensions, Pressure Rating.

A.S.T.M. A197, Material. A153, Galvanizing

Pressure Ratings: 300 p.s.i. – Saturated Steam

1/4" - 1" - 2000 p.s.i. - At 150 Degrees W.O.G.

1 1/4" - 2" - 1500 p.s.i. - At 150 Degrees W.O.G.

2 ½" - 3" - 1000 p.s.i. - At 150 Degrees W.O.G.

U.L. Listed Where Applicable

# Union Specifications: (Brass to Brass, Brass to Iron, Iron to Iron, Gasket Type, Dielectric Iron to Brass)

ANSI B.1.20.1, Threads, B16.39, Dimensions, Pressure Rating. A.S.T.M. A197, Material, A153, Galvanizing.

Federal Spec. WW-U-531

**Pressure Ratings:** Class 150 – 150 p.s.i. – Saturated Steam

300 p.s.i. – At 150 Degrees W.O.G.

Class 250 - 250 p.s.i. - Saturated Steam

500 p.s.i. - At 150 Degrees W.O.G.

Class 300 – 300 p.s.i. – Saturated Steam

600 p.s.i. – At 150 Degrees W.O.G.

U.L. Listed Where Applicable



209, 2nd Floor, Landmark Plaza, Muhammad Bin Qasim Road, Off. I. I. Chundrigar Road, Karachi-74200, Pakistan. Phone: (92-21) 2218028-29, Fax: (92-21) 2218337 E-mail: info@iblink.com.pk, iblink@cyber.net.pk

#### SPECIALIST IN

Carbon Steel
Stainless Steel
Alloy Steel
Low Temperature
&
High Pressure
Materials

# **Cast Iron Specifications**

# CAST IRON FITTINGS

# Standard Class 125 Specifications:

ANSI B1.20.1, Threads. B16.4, Dimensions, Pressure Rating.

A.S.T.M. A126, Material, A153, Galvanizing.

Pressure Ratings: 125 p.s.i. – Saturated Steam

300 p.s.i. – At 150 degrees W.O.G. U.L. Lister

**Federal Spec:** WW-P-501 U.L. Listed Where Applicable

# Plug and Bushing Specifications:

ANSI B1.20.1, Threads. B16.4, Dimensions, Pressure Rating. A.S.T.M. A197(Malleable), A126(Cast) A153 Galvanizing.

Pressure Ratings (Mall.): 125 p.s.i. – Saturated Steam Federal Spec: WW-P-501

300 p.s.i. – At 150 degrees W.O.G. U.L. Listed Where Applicable

Pressure Rating (Cast): 125 p.s.i. – Saturated Steam

175 p.s.i. - At 150 Degrees W.O.G.

# **Drainage Fitting Specifications:**

ANSI B1.20.1, Threads, B16.12, Dimensions. A.S.T.M. A126, Material. A153, Galvanizing

# Cast-Iron Flange Specifications:

ANSI B1.20.1, Threads. B16.1, Dimensions, Pressure Rating.

A.S.T.M. A126, Material, A153, Galvanizing.

Pressure Ratings: 125 p.s.i. – Saturated Steam

175 p.s.i. – At 150 degrees W.O.G.

Federal Spec: WW-P-501 U.L. Listed Where Applicable

Federal Spec: WW-P-941

# **Cast-Iron Flanged Fitting Specifications:**

ANSI B16.1, Dimensions, Pressure Rating.

A.S.T.M. A126 Class B Material.

**Pressure Ratings:** 125 p.s.i. – Saturated Steam

175 p.s.i. – At 150 degrees W.O.G.

**Federal Spec:** WW-F-406 U.L. Listed Where Applicable

209, 2nd Floor, Landmark Plaza, Muhammad Bin Qasim Road, Off. I. I. Chundrigar Road, Karachi-74200, Pakistan. Phone: (92-21) 2218028-29, Fax: (92-21) 2218337 E-mail: info@iblink.com.pk, iblink@cyber.net.pk

**SPECIALIST IN** 

Carbon Steel Stainless Steel Alloy Steel Low Temperature & High Pressure

Materials

# Malleable, Cast Iron, Forged Steel, and Nipple standards & specifications.

# **Standards and Specifications**

	DIMENSIONS	MATERIAL	GALVANIZING	THREAD	PRESSURE RATING	FEDERAL/ OTHER
M.I. Fittings Class 150 Class 300	ANSI B16.3 ANSI B16.3	ASTM A-197 ASTM A-197	ASTM A-153 ASTM A-153	ANSI B.1.20.1+ ANSI B.1.20.1+	ANSI B16.3 ANSI B16.3	WW-P-521
M.I. Unions Class 150 Class 250 Class 300	ANSI B16.39 ANSI B16.39 ANSI B16.39	ASTM A-197 ASTM A-197 ASTM A-197	ASTM A-153 ASTM A-153 ASTM A-153	ANSI B.1.20.1+ ANSI B.1.20.1+ ANSI B.1.20.1+	ANSI B16.39 ANSI B16.39 ANSI B16.39	WW-U-531 WW-U-531 WW-U-531
Cast-Iron Threaded Fitting Class 125 Class 250	js ANSI B16.4 ANSI B16.4	ASTM A-126(A) ASTM A-126(A)	ASTM A-153 ASTM A-153	ANSI B.1.20.1+ ANSI B.1.20.1+	ANSI B16.4 ANSI B16.4	WW-P-501 WW-P-501
C.I. Plugs and Bushings	ANSI B16.14	ASTM A-126(A)	ASTM A-153	ANSI B.1.20.1+	*	WW-P-471
C.I. Drainage Threaded Fi	ttings ANSI B16.12	ASTM A-126(A)	ASTM A-153	ANSI B.1.20.1+	*	WW-P-491
C.I. Flanges and Flanged Class 125 (1"-12") Class 125 (14"-up) Class 250 (1"-12") Class 250 (14"-up)	Fittings ANSI B16.1 ANSI B16.1 ANSI B16.1 ANSI B16.1	ASTM A-126 (A) or (B) ASTM A-126 (B) ASTM A-126 (A) or (B) ASTM A-126 (B)	ASTM -A 153 ASTM -A 153 ASTM -A 153 ASTM -A 153	ANSI B.1.20.1+ ANSI B.1.20.1+ ANSI B.1.20.1+ ANSI B.1.20.1+	ANSI B16.1 ANSI B16.1 ANSI B16.1 ANSI B16.1	WW-F-406 WW-F-406 WW-F-406 WW-F-406
Forged Steel Threaded Fittings Class 2000,3000,6000						
	ANSI B16.11	ASTM A105 A182 A350		ANSI B.1.20.1+	ANSI B16.11	
Pipe Nipples Steel Pipe Welded Welded Seamless Seamless(Hig	ASTM A 733 h Temp.)	ASTM A 53 Type F ASTM A 120 ASTM A 53 Gr. B. Type S ASTM A 106 Gr. B ASTM B 43		ANSI B.1.20.1+	*	WW-N-351**

<sup>\*</sup>The Standard

<sup>\*\*</sup>Compliance with Dimensions and Material Only

<sup>&</sup>quot;+" ANSI B.1.20.1 was ANSI B2.1



209, 2nd Floor, Landmark Plaza, Muhammad Bin Qasim Road, Off. I. I. Chundrigar Road, Karachi-74200, Pakistan. Phone: (92-21) 2218028-29, Fax: (92-21) 2218337 E-mail: info@iblink.com.pk, iblink@cyber.net.pk

## SPECIALIST IN

Carbon Steel
Stainless Steel
Alloy Steel
Low Temperature
&
High Pressure
Materials

# **Nipple Specifications**

# Steel Pipe NIPPLES

# **SPECIFICATIONS**

# **MATERIALS:**

Manufactured in accordance with ASTM Standard Specification A733 - Welded and seamless carbon steel and austenitic stainless steel pipe nipples.

Paragraph 1.1.1 welded carbon steel nipples and 1.1.2 seamless carbon steel nipples.

# **FINISHES**

Anvil steel nipples are available in black, electro galvanized or hot-dipped galvanized finishes. Please specify finish required when ordering.

## **THREADS**

Anvil pipe nipples are threaded on both ends with standard tapered pipe threads conforming to the American Standard for Pipe Threads A.N.S.I. B1.20.1.

Threads are right hand on each end unless otherwise specified. Left hand threads or plain ends or combinations are available.

# **SPECIAL LENGTHS**

Anvil can supply special lengths, special threading and special finishes to order.


# **LENGTH**

Nipples with lengths up through 12 in. long have a length tolerance of +/- 1/10 in. Nipples over 12 in. long have a tolerance of +/- 1/8.


# **IDENTIFICATION**

Where possible, each Anvil seamless pipe nipple is identified with The anvil trademark

Seamless designation "SMLS" Pipe schedule STD, XS, SCH160 and XXS. Material designation A106 B




## **END FINISHES**




# Tapered Pipe Thread(NPT)

Furnished unless special finish requested.




# Straight Pipe Thread



## **Roller Cut**

Furnished when specified on order. (Not deburred.)



# Reamed and Chamfered

Ends sq. cut and bevelled on O.D. at 35° +/- 10° to axis. Inside burrs removed



# **Square Cut**

Ends square cut to central axisall burrs removed

